


Product Highlights

- Operating temperature from -70°C to +150°C (-94°F to +302°F)
- VW-1 according to UL 1441
- FAR 25 § 853
- UL Recognized Component
- Does not trap heat or humidity
- Rot-free
- Expandable design accommodates a variety of sizes

Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)



Expando® HR Plus is an expandable sleeve constructed of Halar® (E-CTFE) fluoropolymer that is designed for applications up to +150°C (+302°F). Inherently flame-retardant, it is a UL Recognized Component which meets VW-1 requirements, and will not melt and drip on direct exposure to flame. Expando HR Plus is a special purpose, highly reliable solution for military and aerospace applications. It offers good mechanical properties, performs well in both high and low temperature environments, and has outstanding chemical resistance.

The patented Bentley-Harris Plus treatment makes end termination neater and easier. The Plus treatment creates a webbing between the filaments of the sleeving to reduce end fray during installation, allowing Expando HR Plus to be cut with ordinary scissors. This reduces assembly time and eliminates the need for proper ventilation equipment required for hot-knife cutting.

Expando HR Plus protective oversleeve has many uses in the aerospace, marine, electronic, military, nuclear and general manufacturing industries.

Expando products are tough, lightweight oversleeves used to protect cable assemblies, hoses and wire harnesses from chafing, cutting and abrading. The open-weave construction of Expando products enables each size to expand to fit several application shapes and sizes. This open-weave construction also makes them highly flexible and resistant to trapping water, heat and humidity.



Office: 866-956-8323

Email: contact@titanelectronics.com

Website: www.titanelectronics.com

ISO 9001:2015 / AS9100D